

ELECTRONICS  
**ARISTO HF35**  
HF GENERATOR

**MEDLIGA**  
медицинское оборудование



**High Efficiency & Flexibility**  
**Intuitive User Interface**  
**10" Touch Screen**  
**Suitable for all Applications in Endoscopy**



Order No.	670-92040
Power Supply	100~240 VAC (110 V optionally)
Frequency	50 Hz (60 Hz optionally)
Nominal Power Consumption	1300 VA +/- 10%
Medical Safety / EMC Standard	EN 60601-1, EN60601-2-2, EN60601-1-2
Safety Classification	IPX2
Classification Type	CF
Approval	CE
Generator Operation Frequency	333 kHz
Weight of Main Unit	Approx. 14.0 kg
Dimensions of Main Unit (W x H x D)	470 x 210 x 420 mm
Operation Temperature / Humidity	+10°C ~ +40°C / 10% ~ 90%
Storage Temperature / Humidity	-20°C ~ +50°C / 10% ~ 90%
Mono Cut	350 W
Precise Cut	50 W
Mixed Cut	150 W
Argon Cut	350 W
Argon Coag	80 W
Mono Soft Coag	200 W
Mono Forced Coag	200 W
Mono Hybrid Coag	200 W
Bipolar Cut	120 W
Bipolar Soft Coag (Auto Start / Stop)	120 W
Bipolar Forced Coag	120 W
ThermoStapling	300 W
User Interface	10" Touch Screen
Language	10 for Display, 2 for Voice Messaging
Output for Instruments	SCC x 2, 3-Pin Monopolar x 1, 2-Pin Bipolar x 1
Argon Output	1 x Luer Lock Connector
Argon Supply Input	2 x Connections
Neutral Electrode Socket	Flat plug acc. US Standard
2 Pedal Foot Switch Wireless	670-92051
2 Pedal Foot Switch Wire	670-92052
1 Pedal Foot Switch Wire	
Extend of Delivery	Main Unit, Power Cable, User Manual



Работайте с лучшими,  
всё остальное компромисс!

---

**8 (800) 775-10-98**

**medliga.ru**